



(slika je simbolična)

[krogelni ventil medenina, električni vklop, 230 V AC, 50 Hz, Rp 1](#)

Kategorija: [Brass ball valve, electric actuator 230 VAC, 50 Hz](#)Šifra: **103696RIE**

Kratek opis

Brass ball valve, Electr. actuation drive, 230 V AC, 50 Hz,
Operating temperature -20 °C to 70 °C, Rp 1, DN 25, PN
max. 40 bar
Voltage range 230 VAC, 50 Hz or 24 VDC.
2-way cock, full bore, for neutral gases and liquids.
Reversible electric rotary actuator.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-30
Min. delovna temperatura [°C]	-20
Gred izbirnika	Hard chrome-plated brass
Indikator položaja IP zaščita	Manually operated IP 68
Krogelno tesnilo	PTFE, glass fibre-reinforced
Krogla	Hard chrome-plated brass
Material	Nickel-plated brass
Montažna prirobnica	ISO 5211
Navoj	Rp 1
Ohišje	Aluminium powder-coated
Tesnilo gredi izbirnika	FKM
Čas aktivacije [sec.]	15
D [mm]	25.0
DN	25
Delovni cikel [%]	30
Relativna vlažnost	30 % to 95 %
PN [bar]	40
a/f [mm]	41
Max. delovna temperatura [°C]	70
Max. sobna temperatura [°C]	70
L [mm]	90.0
A [mm]	153.0
B [mm]	170.5
Napetost	230 VAC, 50 Hz