

Datum: 02.10.2024



krogelni ventil medenina, električni vklop, 24 V DC, Rp 1 1/4

Kategorija: [Brass ball valve with electric actuator 24 VDC](#)
Šifra: **103703RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Electrical actuation drive, 24 V DC,
Operating temperature -20 °C to 70 °C, Rp 1 1/4, DN 32, PN
max. 40 bar
Voltage range 230 VAC, 50 Hz or 24 VDC.
2-way cock, full bore, for neutral gases and liquids.
Reversible electric rotary actuator.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-30
Min. delovna temperatura [°C]	-20
Gred izbirnika	Hard chrome-plated brass
Indikator položaja IP zaščita	Manually operated IP 68
Krogelno tesnilo	PTFE, glass fibre-reinforced
Krogla	Hard chrome-plated brass
Material	Nickel-plated brass
Montažna prirobnica	ISO 5211
Navoj	Rp 1 1/4
Ohišje	Aluminium powder-coated
Tesnilo gredi izbirnika	FKM
Čas aktivacije [sec.]	20
Napetost	24 VDC
D [mm]	30.0
Delovni cikel [%]	30
Relativna vlažnost	30 % to 95 %
DN	32
PN [bar]	40
a/f [mm]	50
Max. delovna temperatura [°C]	70
Max. sobna temperatura [°C]	70
L [mm]	110.0
A [mm]	153.0
B [mm]	181.5