

krogelni ventil medenina, pnevmatski vklop duble-acting, Rp 1 1/2

Kategorija: [Brass ball valve, double-acting actuator](#)
Šifra: **158801RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, double-acting, Operating temp. -20°C to 150°C, Rp 1 1/2, DN 40, PN max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR Nickel-plated brass, with flange plate ISO 5211
Material krogelnega ventila	Rp 1 1/2
Navoj	Anodised aluminium
Pogonski material	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.6
Priporočeni vodeni tlak [bar]	8.4
Max. vodeni tlak aktuatorja [bar]	16
Max. delovni tlak krogelnega ventila [bar]	40
DN	80
Max. delovna temperatura aktuatorja [°C]	90
Kot vrtenja [°]	114.0
L [mm]	129.8
B [mm]	150
Max. delovni tlak krogelnega ventila [°C]	159.0
A [mm]	