

Datum: 02.10.2024



[krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 1 1/2](#)

Kategorija: [Brass ball valves, double-acting actuator](#)
Šifra: **103528RIE**

(slika je simbolična)

Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70°C, Rp 1 1/2, DN 40, PN max. 25 bar
2-way cock, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	25
D [mm]	36.0
DN	40
a/f [mm]	55
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	120.0
A [mm]	133.0
B [mm]	166.0