

Datum: 03.11.2024

krogelni ventil medenina, pnevmatski vklop duble-acting, Rp 1/2

Kategorija: [Brass ball valve, double-acting actuator](#)Šifra: **158829RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, double-acting,
Operating temperature -20 °C to 150 °C, Rp 1/2, DN 15, PN
max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Supplied as standard Nickel-plated brass, with flange plate ISO 5211
Material krogelnega ventila	Rp 1/2
Navoj	Anodised aluminium
Pogonski material	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.6
Priporočeni vodeni tlak [bar]	8.4
Max. vodeni tlak aktuatorja [bar]	15
DN	16
Max. delovni tlak krogelnega ventila [bar]	69.0
L [mm]	70.0
A [mm]	80
Max. delovna temperatura aktuatorja [°C]	88.0
B [mm]	90
Kot vrtenja [°]	150
Max. delovni tlak krogelnega ventila [°C]	