

Datum: 03.07.2024



[krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 2 1/2](#)

Kategorija: [Brass ball valves, double-acting actuator](#)
Šifra: **10353ORIE**

(slika je simbolična)

Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70°C, Rp 2 1/2, DN 65, PN max. 25 bar
2-way cock, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 2 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	25
D [mm]	57.0
DN	65
Max. delovna temperatura [°C]	70
a/f [mm]	83
Kot vrtenja [°]	90
L [mm]	155.0
A [mm]	161.0
B [mm]	213.0