

krogelni ventil medenina, pnevmatski vklop duble-acting, Rp 2

Kategorija: [Brass ball valve, double-acting actuator](#)
Šifra: **158802RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, DN 50, PN max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR Nickel-plated brass, with flange plate ISO 5211
Material krogelnega ventila	Rp 2
Navoj	Anodised aluminium
Pogonski material	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.6
Priporočeni vodeni tlak [bar]	8.4
Max. vodeni tlak aktuatorja [bar]	16
Max. delovni tlak krogelnega ventila [bar]	50
DN	80
Max. delovna temperatura aktuatorja [°C]	90
Kot vrtenja [°]	134.0
L [mm]	143.8
B [mm]	150
Max. delovni tlak krogelnega ventila [°C]	174.2
A [mm]	