

Datum: 02.10.2024



(slika je simbolična)

## [krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 3/4](#)

Kategorija: [Brass ball valves, double-acting actuator](#)  
Šifra: **103523RIE**

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70 °C, Rp 3/4, DN 20, PN max. 40 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 3/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	20.0
DN	20
a/f [mm]	32
PN [bar]	40
Max. delovna temperatura [°C]	70
L [mm]	80.0
Kot vrtenja [°]	90
A [mm]	133.0
B [mm]	145.0