

Datum: 22.07.2024



## krogelni ventil medenina, pnevmatski vklop vzmetni preklop, Rp 2

Kategorija: [Brass ball valve, single-acting actuator](#)  
Šifra: **103537RIE**

(slika je simbolična)

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring switching, Operating temp. max. 70 °C, Rp 2, DN 50, PN max. 25 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	25
D [mm]	45.0
DN	50
a/f [mm]	70
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	140.0
A [mm]	180.0
B [mm]	203.0