

Datum: 21.12.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## krogelni ventil medenina, pnevmatski vklop vzmetni preklop, Rp 3

Kategorija: [Brass ball valve, single-acting actuator](#)  
Šifra: **103539RIE**

(slika je simbolična)

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring switching, Operating temp. max. 70 °C, Rp 3, DN 80, PN max. 16 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                                   |  |
|-----------------------------------|--|
| Min. delovna temperatura [°C]     | -20  |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 3                                       |
| Pogonski material                 | Anodised aluminium                         |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR  |
| Različica                         | single-acting - spring to close            |
| Priporočeni vodeni tlak [bar]     | 5.5  |
| Max. vodeni tlak aktuatorja [bar] | 10   |
| PN [bar]                          | 16   |
| D [mm]                            | 68.0                                       |
| Max. delovna temperatura [°C]     | 70   |
| DN                                | 80   |
| Kot vrtenja [°]                   | 90   |
| a/f [mm]                          | 98   |
| L [mm]                            | 182.0                                      |
| A [mm]                            | 209.0                                      |
| B [mm]                            | 242.0                                      |