

Datum: 03.07.2024

krogelni ventil nerjavno jeklo, električni vklop, 24 V DC

Kategorija: [Stainless steel ball valve, elect. actuator 24 VDC](#)
Šifra: **103713RIE**

(slika je simbolična)

Kratek opis

2-way stainless steel ball valve, Electr. actuation drive, 24 V DC, Medium temp. -10 °C to 200 °C, Rp 3/4, DN 20, PN max. 63 bar
Voltage range 230 VAC, 50 Hz or 24 VDC.
Reversible electric rotary actuator.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-30
Min. temperatura medija [°C]	-10
Dolžina	DIN 3203 - M3
Indikator položaja	Manually operated
IP zaščita	IP 68
Krogelno tesnilo	PTFE, glass fibre-reinforced
Material	Stainless steel 1.4401 / 1.4408
Montažna prirobnica	ISO 5211
Navoj	Rp 3/4
Ohišje	Aluminium powder-coated
Tesnilo gredi izbirnika	PTFE, glass fibre-reinforced
D [mm]	17.5
Čas aktivacije [sec.]	20
DN	20
Napetost	24 VDC
Delovni cikel [%]	30
Relativna vlažnost	30 % to 95 %
a/f [mm]	35
Max. obratovalni tlak [bar]	63
Max. sobna temperatura [°C]	70
L [mm]	80.0
A [mm]	153.0
B [mm]	153.0
Max. temperatura medija [°C]	200