



(slika je simbolična)

## krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 1

Kategorija: [Stainless steel ball valve, double-acting actuator](#)  
Šifra: **103599RIE**

### Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20 °C to 70 °C, Rp 1, PN max. 63 bar  
2-way cock, 3-piece, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.  
Standardised interfaces:  
Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.  
Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.  
Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 1
Navoj	Anodised aluminium
Pogonski material	PTFE
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.5
Priporočeni vodeni tlak [bar]	10
Max. vodeni tlak aktuatorja [bar]	25
DN	30.0
D [mm]	41
a/f [mm]	63
Max. obratovalni tlak [bar]	70
Max. delovna temperatura [°C]	90
Kot vrtenja [°]	90.0
L [mm]	133.0
A [mm]	157.0
B [mm]	