

Datum: 24.08.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 1 1/4

Kategorija: [Stainless steel ball valve, double-acting actuator](#)
Šifra: **103600RIE**

(slika je simbolična)

Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20°C to 70°C, Rp 1 1/4, PN max 63 bar

2-way cock, 3-piece, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

| | |
|-----------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Acc. to NAMUR Stainless steel |
| Material krogelnega ventila | 1.4401, with ISO flange plate Rp 1 1/4 |
| Navoj | Anodised aluminium |
| Pogonski material | PTFE |
| Premaz za krogelni ventil | NBR |
| Premaz za pogon | double-acting |
| Različica | 5.5 |
| Priporočeni vodeni tlak [bar] | 10 |
| Max. vodeni tlak aktuatorja [bar] | 32 |
| DN | 37.0 |
| D [mm] | 50 |
| a/f [mm] | 50 |
| Max. obratovalni tlak [bar] | 63 |
| Max. delovna temperatura [°C] | 70 |
| Kot vrtenja [°] | 90 |
| L [mm] | 110.0 |
| A [mm] | 137.0 |
| B [mm] | 176.0 |