

Datum: 02.10.2024



(slika je simbolična)

[krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1/2](#)

Kategorija: [Stainless steel ball valve, double-acting actuator](#)Šifra: **103582RIE**

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 160 bar
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila Material	Supplied as standard Stainless steel
krogelnega ventila	1.4401/1.4301/1.4310/1.4408, with ISO flange
Navoj	Rp 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.6
DN	15
L [mm]	61.0
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
A [mm]	114.0
B [mm]	139.0
Max. delovna temperatura [°C]	150
PN [bar]	160