

Datum: 24.08.2024



(slika je simbolična)

## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 2

Kategorija: [Stainless steel ball valve, double-acting actuator](#)Šifra: **103587RIE**

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, PN max. 40 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Navoj	Rp 2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.6
PN [bar]	40
DN	50
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
L [mm]	125.0
Max. delovna temperatura [°C]	150
A [mm]	169.0
B [mm]	196.0