

Datum: 27.07.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 1 1/2

Kategorija: [Ball valves 3-piece, length acc. to DIN 3202-M3](#)
Šifra: **135916RIE**

Kratek opis

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 1 1/2, DN 40, Operating temp. -20 °C to 180 °C, PN max. 63 bar

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.7 mm
Krogelno tesnilo	F 05 / F 07 PTFE (15 % glass fibre reinforced)
Krogla	Stainless steel 1.4401
Navoj	G 1 1/2
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211
Stebelno tesnilo	PTFE
C Ø [mm]	38.0
DN	40
PN [bar]	63
B [mm]	113.5
L [mm]	120.0
Max. delovna temperatura [°C]	180
A [mm]	190.0