

Datum: 22.07.2024



(slika je simbolična)

## [krogelni ventil robustnejša oblika, Z ročico, ročni, IT/IT, G 1/2](#)

Kategorija: [Ball valve with hand lever, IT/IT](#)  
Šifra: **103263RIE**

### Kratek opis

Ball valve heavy duty design, Manual lever, IT/IT, nickel-plated brass, Operating temp. -20 °C to 130 °C, G 1/2, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

### Tehnične Specifikacije

|                               |                                   |
|-------------------------------|-----------------------------------|
| Min. delovna temperatura [°C] | -20                               |
| Krogelno tesnilo              | PTFE                              |
| Krogla                        | Chrome-plated brass               |
| Material navojev              | Brass with a bare metal surface   |
| Navoj                         | G 1/2                             |
| Ohišje                        | Nickel-plated brass               |
| Ročica                        | Aluminium, painted black          |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo              | PTFE                              |
| E [mm]                        | 9.5                               |
| F [mm]                        | 9.5                               |
| DN                            | 15                                |
| a/f [mm]                      | 26                                |
| L [mm]                        | 55.0                              |
| B [mm]                        | 64.0                              |
| PN [bar]                      | 80                                |
| A [mm]                        | 100.0                             |
| Max. delovna temperatura [°C] | 130                               |