

Datum: 26.12.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krogelni ventil stinardna obilka, črna jeklena ročica, IT/ET, G 1](#)

Kategorija: [Ball valve with black steel lever, IT/ET](#)
Šifra: **103199RIE**

Kratek opis

Ball valve standard design, black steel lever, IT/ET, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 1, PN max. 40 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material	Nickel-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 1
Ročica	Steel, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
E [mm]	12.0
F [mm]	12.0
DN	25
PN [bar]	40
B [mm]	52.3
L [mm]	78.8
Max. delovna temperatura [°C]	90
A [mm]	105.0