

**Datum:** 02.10.2024



(slika je simbolična)

## [krogelni ventil, visoki tlak, težka izvedba, M18x1.5](#)

Kategorija: [High-pressure ball valve, steel, heavy-duty series](#)  
Šifra: **103507RIE**

### Kratek opis

Ball valve, High pressure design, Heavy-duty series, Steel,  
Operating temp. -10 °C to 100 °C, M18x1.5, DN 6, PN max.  
500 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	M18x1.5
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	6
O.D. za cevi [mm]	10S
B [mm]	55.0
L [mm]	73.0
A [mm]	76.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	500