

Datum: 03.07.2024



(slika je simbolična)

[krogelni ventil, visoki tlak, težka izvedba, M24x1.5](#)

Kategorija: [High-pressure ball valve, steel, heavy-duty series](#)
Šifra: **103510RIE**

Kratek opis

Ball valve, High pressure design, Heavy-duty series, Steel,
Operating temp. -10 °C to 100 °C, M24x1.5, DN 12, PN max.
500 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	M24x1.5
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	12
O.D. za cevi [mm]	16S
L [mm]	87.0
B [mm]	92.0
Max. delovna temperatura [°C]	100
A [mm]	112.0
Max. obratovalni tlak [bar]	500