

Datum: 22.07.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## [krogelni ventil, visoki tlak, težka izvedba, M36x2](#)

Kategorija: [High-pressure ball valve, steel, heavy-duty series](#)  
Šifra: **103512RIE**

### Kratek opis

Ball valve, High pressure design, Heavy-duty series, Steel,  
Operating temp. -10 °C to 100 °C, M36x2, DN 20, PN max.  
420 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	M36x2
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	20
O.D. za cevi [mm]	25S
Max. delovna temperatura [°C]	100
L [mm]	107.0
B [mm]	121.0
A [mm]	187.0
Max. obratovalni tlak [bar]	420