

Datum: 03.07.2024



(slika je simbolična)

[krogelni ventil z podaljšanim navojem, IT/ET, Rp/R 3/8](#)

Kategorija: [Ball valve, long-threaded type, IT/ET](#)
Šifra: **103246RIE**

Kratek opis

Ball valve long thread design, IT/ET, nickel-plated brass,
Operating temperature -15 °C to 90 °C, Rp/R 3/8, DN 10, PN
max. 40 bar
Applications: Compressed air, water, non-toxic and non-
corrosive gases, heating systems, agriculture.

Tehnične Specifikacije

| | |
|-------------------------------|---------------------------------|
| Min. delovna temperatura [°C] | -15 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Brass with a bare metal surface |
| Navoj | Rp/R 3/8 |
| Ročica | Aluminium, painted black |
| Standardni navoj | Thread acc. to ISO 7-1 |
| Stebelno tesnilo | HNBR / EPDM / PTFE |
| DN | 10 |
| Max. obratovalni tlak [bar] | 40 |
| B [mm] | 42.0 |
| L [mm] | 54.0 |
| A [mm] | 85.0 |
| Max. delovna temperatura [°C] | 90 |