

Datum: 03.07.2024



krogelni ventil z vgrajenim izpustom, nikljana medenina, G 2

Kategorija: [Ball valves with integrated strainer](#)
Šifra: **133559RIE**

(slika je simbolična)

Kratek opis

Ball valve, integrated strainer, nickel-plated brass,
Operating temp. -20 °C to 100 °C, G 2, DN 46, PN max. 20 bar, Mesh size 0.5
Space and cost saving combination made of ball valve and dirt strainer in one.
Replaces the sequence of ball valve - dirt strainer - ball valve and thus reduces installation time and costs.
The can be removed easily in locked, pressure released status for cleaning.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Nickel-plated brass (CW617N)
Navoj	G 2
Ohišje	Nickel-plated brass (CW617N)
Ročica	Galvanised steel with plastic coating
Standardni navoj	G-thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	NBR / FKM
Zaslon	Stainless steel, mesh size 0.5 mm
E [mm]	20.0
PN [bar]	20
DN	46
a/f 2 [mm]	65
a/f 1 [mm]	66
D [mm]	68.5
B [mm]	88.5
Max. delovna temperatura [°C]	100
L [mm]	117.0
A [mm]	158.0