



(slika je simbolična)

Manometer, robustna verzija, G 1/2, 0 - 10 bar, Ø 160

Kategorija: [Wika](#)Šifra: **102046RIE**

Kratek opis

Pressure gauge, robust design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0 - 10 bar, Ø 160 Robust bourdon-tube pressure gauge. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|-----------------------|
| Min. sobna temperatura [°C] | -40 |
| Min. temperatura medija [°C] | -40 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | CrNi steel |
| Položaj povezave | radial on bottom |
| Povezava | G 1/2 |
| Prednje steklo | Flat instrument glass |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.2 |
| Razred točnosti | 1.0 |
| Merilno območje max. bar | 10 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 80 |
| Premer [mm] | 160 |
| Vrsta | 212.20 |