

Datum: 24.08.2024



(slika je simbolična)

Manometer, robustna verzija, G 1/2, -1 / +1.5 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **102017RIE**

Kratek opis

Pressure gauge, robust design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range -1 / +1.5 bar, Ø 100

Robust bourdon-tube pressure gauge.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-40
Min. temperatura medija [°C]	-40
Merilno območje min. bar	-1
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Flat instrument glass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Vacuum/Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.05
Razred točnosti	1.0
Merilno območje max. bar	1.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	80
Premer [mm]	100
Vrsta	212.20