

Datum: 24.08.2024



(slika je simbolična)

Medprirobnični zaporni ventil, Pneum. vklop, DN 125

Kategorija: [Butterfly valve, with single-acting actuator](#)
Šifra: **103679RIE**

Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, single-acting, Operating temp. -15°C to 120°C, DN 125, PN max. 16 bar

Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.

For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.

Not recommended for hydrocarbons, oils or greases.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -15 |
| Adapter ventila | Supplied as standard, operated by a 3/2- or 5/2-way valve |
| Disc | Stainless steel |
| Gred izbirnika | CF8M/1.4404 |
| Ohišje | SS416 |
| Pogonski material | Grey cast iron GG25 |
| Premaz za pogon | epoxy resin coated, RAL 5015 color |
| Različica | Anodised aluminium |
| Tesnilo | NBR |
| Tesnilo gredi izbirnika | single-acting - spring to close |
| Min. vodeni tlak [bar] | EPDM |
| Max. vodeni tlak [bar] | EPDM |
| Max. obratovalni tlak [bar] | 5 |
| B [mm] | 5.5 |
| Kot vrtenja [°] | 16 |
| Max. delovna temperatura [°C] | 59.0 |
| H1 [mm] | 90 |
| DN | 120 |
| L [mm] | 123.0 |
| H2 [mm] | 125 |
| H3 [mm] | 190.0 |
| | 191.0 |
| | 361.0 |