



(slika je simbolična)

MikroFilter »FUTURA-mali«, z PC zbiralnik, Velikost 0, G 1/4

Kategorija: [Microfilter with polycarbonate bowl](#)
Šifra: **142449RIE**

Kratek opis

Microfilter »FUTURA-mini«, PC container, 0.01 μm , Size 0, G 1/4, Input pressure 1.5 - 12 bar, Temp. -10°C to 50°C, Fully-automatic

Micro-filters in modern design for compliance with strict compressed air purity requirements.

Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 μm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Borosilicate glass fibre
Ločevanje prahu	> 0.01 μm 99.999 % At $P_2 = 6$ bar and pressure drop $\Delta p = 0.1$ bar
Merjenje pretoka	G 1/4
Navoj	Fully-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Polycarbonate container
Posoda	Plastic
Priključni navoj	FUTURA-mini
Serijska	Compressed air, neutral gases
Srednje	NBR
Tesnilo	
Vsebnost olja v ostanku [mg/m ³]	< 0.01
Rang filtra [μm]	0.01
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	12
C [mm]	27.0
A [mm]	43.0
Max. temperaturno območje [°C]	50
B [mm]	170.0
Pretok [l/min]	190