



(slika je simbolična)

MikroFilter »multifix«PC zbir.Protec. cageVel.1,G 1/4

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)
Šifra: **100535RIE**

Kratek opis

Microfilter »multifix«, PC container and protective cage, 0.01 μm , Size 1, G 1/4, Input pressure max. 16 bar, Temp. max. 60 °C
For filtering out solid impurities larger than 0.01 μm .

Tehnične Specifikacije

Element filtra	Borosilicate-POM
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Serija	multifix
Tesnilo	NBR
Rang filtra [μm]	0.01
Vsebnost olja v ostanku [mg/m^3]	0.01
Velikost	1
DN	6
Max. vhodni tlak [bar]	16
C [mm]	27.0
A [mm]	47.8
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Učinkovitost [%]	99.999
D [mm]	125.1
B [mm]	152.1
Pretok [l/min]	280