



(slika je simbolična)

MikroFilter »variobloc«Kov. pos.0.01 µmVel.1,G 1/4

Kategorija: [Microfilter with metal bowl, incl. sight glass](#)
Šifra: **125320RIE**

Kratek opis

Microfilter »variobloc«, Metal container incl. viewing tube, 0.01 µm, Size 1, G 1/4, Input pressure max. 20 bar, Temp. max. 50 °C
Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.
As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Tehnične Specifikacije

| | |
|------------------------------|---|
| Kakovost zraka po ISO 8573.1 | Class 1 dirt, class 1 oil |
| Merjenje pretoka | At $P_1 = 7$ bar and pressure drop $\Delta p = 0,1$ bar |
| Navoj | G 1/4 |
| Posoda | Metal container with viewing tube |
| Serija | variobloc |
| Rang filtra [µm] | 0.01 |
| Velikost | 1 |
| Max. vhodni tlak [bar] | 20 |
| C [mm] | 22.0 |
| A [mm] | 48.0 |
| Max. temperatura medija [°C] | 50 |
| Max. sobna temperatura [°C] | 80 |
| Učinkovitost [%] | 99.999 |
| B [mm] | 155.0 |
| Pretok [l/min] | 370 |