

Datum: 22.07.2024



MikroFilter za visoke pritiske do 60 bar, 0.01 µm, G 1/2

Kategorija: [Microfilters for high pressures up to 60 bar](#)Šifra: **101181RIE**

(slika je simbolična)

Kratek opis

Microfilter for high pressures up to 60 bar, manual bleeder valve, 0.01 µm, G 1/2, Brass container, Operating temp. 0 °C to 90 °C

Fine filter for all applications with particularly strict compressed air purity requirements. Micro-filters should always be used in conjunction with a standard filter connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Element filtra | Borosilicate |
| Merjenje pretoka | At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.5$ bar |
| Navoj | G 1/2 |
| Ohišje | Aluminium |
| Posoda | Brass |
| Tesnilo | NBR |
| Rang filtra [µm] | 0.01 |
| C [mm] | 25.0 |
| Max. vhodni tlak [bar] | 60 |
| A [mm] | 65.0 |
| Max. delovna temperatura [°C] | 90 |
| Učinkovitost [%] | 99.9999 |
| B [mm] | 187.0 |
| Pretok [l/min] | 2000 |