

Datum: 22.07.2024



(slika je simbolična)

## Mini izpu.vent., 1.4305, G 1/4, vkl. prit. 0.5 - 1 bar

Kategorija: [Stainless steel blow off safety valve, G 1/4](#)  
Šifra: **103922RIE**

### Kratek opis

Mini bleeder valve, Stainless steel, not component checked,  
Operating temp. -20 °C to 180 °C, G 1/4, Trigger pressure  
0.5 - 1 bar

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases,  
cannot be used for liquids due to free blow-off, not suitable  
for steam.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Material	Stainless steel
	1.4305
Navoj	G 1/4
Tesnilo	FKM
Vzmet	Stainless steel
	1.4310
Min. nastavljeni tlak [bar]	0.5
Min. obratovalni tlak [bar]	0.5
Max. nastavljeni tlak [bar]	1
narediti [mm]	3.0
D [mm]	7.0
a/f [mm]	16
C [mm]	27.0
Hitrost izpiranja max. [l/min]	50
Max. obratovalni tlak [bar]	60
Max. delovna temperatura [°C]	180