



(slika je simbolična)

Mini izpu.vent., 1.4305, G 1/4, vkl. prit. 16 - 32 bar

Kategorija: [Stainless steel blow off safety valve, G 1/4](#)
Šifra: **103927RIE**

Kratek opis

Mini bleeder valve, Stainless steel, not component checked,
Operating temp. -20 °C to 180 °C, G 1/4, Trigger pressure
16 - 32 bar
Manual adjustment of the blow-off pressure (lock nut).
For compressed air and non-toxic, non-flammable gases,
cannot be used for liquids due to free blow-off, not suitable
for steam.

Tehnične Specifikacije

| | |
|--------------------------------|-----------------|
| Min. delovna temperatura [°C] | -20 |
| Material | Stainless steel |
| | 1.4305 |
| Navoj | G 1/4 |
| Tesnilo | FKM |
| Vzmet | Stainless steel |
| | 1.4310 |
| Min. obratovalni tlak [bar] | 0.5 |
| narediti [mm] | 3.0 |
| D [mm] | 7.0 |
| a/f [mm] | 16 |
| Min. nastavljeni tlak [bar] | 16 |
| C [mm] | 27.0 |
| Max. nastavljeni tlak [bar] | 32 |
| Max. obratovalni tlak [bar] | 60 |
| Max. delovna temperatura [°C] | 180 |
| Hitrost izpiranja max. [l/min] | 1600 |