

CEV PRIMOFLEX® 3/4" - 25 M

Kakovostna vrtna cev PrimoFlex® (3/4") dolžine 25 m s tlačno odporno tkano ojačitvijo, ki je zdravju neškodljiva. Razpočni tlak: 24 barov. Visoka temperaturna odpornost od -20 do +65 °C.



Številka naročila

2.645-142.0

Tehnični podatki

		4039784447622
Premer		3/4"
Dolžina cevi	m	25
Teža	Kg	5,39
Teža vključno z embalažo	Kg	5,435
Mere (D × Š × V)	mm	380 × 380 × 155

12 let garancije

- Zagotovljena dolga življenjska doba

3 sloji

- Odpornost proti prelomom

Prenese tlak do 24 barov

- Trpežnost zagotovljena

KOMPATIBILNE NAPRAVE

- K 2 Battery
- K 2 Battery Set
- K 7 Compact
- K 7 Compact Home
- K 7 Premium Smart Control
- K 7 Premium Smart Control Home
- K 7 Smart Control
- K 7 Smart Control Home
- K 7 WCM
- K 7 Power
- K 7 Premium Power
- K 7 Premium Power Home
- K 7 WCM Premium
- K 7 WCM Premium Home
- K 5 Compact
- K 5 Compact Home
- K 5 Compact Home Flex Anti-Twist
- K 5 Premium Smart Control
- K 5 Premium Smart Control Home
- K 5 Power Control
- K 5 Power Control Home
- K 5 Smart Control
- K 5 Smart Control Home
- K 5 Premium Power Control
- K 5 Premium Power Control Home
- K 5 WCM Premium
- K 5 WCM Premium Home
- K 5 WCM
- K 4 Premium Power Control
- K 4 Premium Power Control Home
- K 4 Power Control
- K 4 Power Control Home
- K 4 WCM Premium
- K 4 WCM Premium Home
- K 4 WCM
- K 3 Power Control
- K 3 Power Control Home
- K 3 Premium Power Control
- K 3 Premium Power Control Home
- K 2 Universal Edition
- K 2 Premium Power Control
- K 2 Premium Power Control Home
- K 2 Power Control
- K 2 Power Control Home
- K Mini
- K Mini Plus
- G 7.180
- SP 1 Dirt
- SP 22.000 Dirt Level Sensor
- SP 22.000 Dirt
- SP 16.000 Dirt
- SP 16.000 Flood Box
- SP 11.000 Dirt
- SP 9.500 Dirt
- SP 16.000 Dual
- SP 17.000 Flat Level Sensor
- SP 9.000 Flat