



Naoljevalnik »FUTURA« Kov. pos. Kazalno okence Vel. 2, G 1/2

Kategorija: [Oil-mist lubricator with metal bowl, sight glass](#)Šifra: **139515RIE**

(slika je simbolična)

Kratek opis

Mist oiler »FUTURA«, with metal container and viewing tube, Size 2, G 1/2, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Oil-mist lubricators with excellent flow rates in modern design.

These devices can be used to top up oil automatically.

A hose must be connected to the threaded nipple on the oil bowl for this purpose.

When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Merjenje pretoka | At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/2 |
| Ohišje | PA66 GF60 |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Razred olja | CL 32 acc. to DIN 51517-ISO VG 32 |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Vidna kupola | PC |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 16 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 63.0 |
| C [mm] | 70.0 |
| B [mm] | 215.0 |
| Pretok [l/min] | 8000 |