

Datum: 24.08.2024



(slika je simbolična)

Naoljevalnik »multifix« PC zbir. Protec. cage Vel.4, G 3/4

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)Šifra: **133119RIE**

Kratek opis

Mist oiler »multifix«, PC container and protective cage, Size 4, G 3/4, Input pressure max. 16 bar, Med./ambient temp. max. 60 °C
Proportional lubricators, oil can be filled under pressure.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Ohišje | Die-cast aluminium |
| Posoda | Polycarbonate container with protective cage |
| Razred olja | CL 32 acc. to DIN 51517-ISO VG 32 |
| Serija | multifix |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Velikost | 4 |
| Max. vhodni tlak [bar] | 16 |
| DN | 20 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 85.0 |
| C [mm] | 86.0 |
| D [mm] | 182.0 |
| B [mm] | 268.0 |
| Pretok [l/min] | 14000 |