

Datum: 24.08.2024

Naoljevalnik »variobloc«PC zbir.Protec. cageVel. 2G 3/4

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)
Šifra: **124819RIE**

(slika je simbolična)

Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 2, G 3/4, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj | G 3/4 |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container with protective cage |
| Razred olja | CL 32 acc. to DIN 51517-ISO VG 32 |
| Serija | variobloc |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 16 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| C [mm] | 57.0 |
| A [mm] | 70.0 |
| B [mm] | 224.0 |
| Pretok [l/min] | 7500 |