

Datum: 03.07.2024



## Naoljevalnik »variobloc« z PC zbiralnik, Velikost 1, G 3/8

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)  
Šifra: **100704RIE**

(slika je simbolična)

### Kratek opis

Mist oiler »variobloc« with polycarbonate container, Size 1, G 3/8, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serijska	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	1
Max. vhodni tlak [bar]	16
A [mm]	48.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	52.0
B [mm]	171.0
Pretok [l/min]	4400