

Datum: 03.11.2024



(slika je simbolična)

## Natančen Tlačni reg. »variobloc« Vel.2, G 1/2, 0.2-6 bar

Kategorija: [Precision pressure regulators](#)Šifra: **149220RIE**

### Kratek opis

Precision pressure regulator »variobloc«, incl. pressure gauge, Size 2, G 1/2, Input pressure max. 25 bar, Control range 0.2-6 bar

Pre-pressure independent, reversible diaphragm pressure regulator with secondary venting for applications that require a precise pressure regulation. The line pressure is regulated by the pressure regulator to the set working pressure/secondary pressure and maintains this constantly regardless of pressure fluctuations and air consumption. The precision pressure regulator is characterised by a very low internal air consumption (< 1.5 l/min).

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Poraba zraka	Yes
Serijska	variobloc
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.2
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Velikost	2
Max. krmilno območje [bar]	6
Zaslon manometra max. [bar]	6
Max. vhodni tlak [bar]	25
C [mm]	33.0
A [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	134.0
Pretok [l/min]	7000