

Datum: 03.11.2024



(slika je simbolična)

Natančen Tlačni reg.G 3/8Regulacijsko območje 0.05 - 7 bar

Kategorija: [Precision pressure regulators \(high flow rate\)](#)Šifra: **101237RIE**

Kratek opis

Precision pressure regulator without pressure gauge, G 3/8, Control range 0.05 - 7 bar, Input pressure max. 16 bar With high flow rate and large secondary venting. Diaphragm pressure regulators with large secondary venting for applications requiring an extremely accurate working pressure, especially at high flow rates.

Tehnične Specifikacije

Navoj	G 3/8
Navoj manometra	G 1/4
Odzračevalni vtič	G 3/8 (for mounting a silencer)
Ohišje	Die-cast zinc
Poraba zraka	Yes
Srednje	Micro-filtered, unooled compressed air (0.01 µm)
Tesnilo	NBR
Min. krmilno območje [bar]	0.05
Max. notranja poraba zraka	1.5 - 6 l/min, depending on input pressure and control range
Max. krmilno območje [bar]	7
Max. vhodni tlak [bar]	16
C [mm]	43.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	82.0
D [mm]	159.0
B [mm]	202.5
Pretok [l/min]	5500