

Datum: 02.10.2024



(slika je simbolična)

## Nav. priklj. 331, N.N./Z.N.Rp/R 1 1/2,č. kovanlit. ž.

Kategorija: [Union 331, flat seat, female/male, with NBR-seal](#)  
Šifra: **113176RIE**

### Kratek opis

Fitting 331, flat sealing, IT/ET, Rp/R 1 1/2, NBR seal,  
Operating temp. -20°C to 200°C, black malleable cast iron,  
Hot-dip galva.

"

Maximum temperature and maximum operating pressure  
should not occur at the same time!

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for  
pipe construction.

These fittings are characterized by their high mechanical  
strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are  
therefore suitable for drinking water

### Tehnične Specifikacije

|                                   |   |
|-----------------------------------|---|
| Min. temperaturno območje<br>[°C] | -20   |
| Material                          | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj                             | Rp/R 1 1/2  |
| Površina                          | Hot dip galvanised                                  |
| Standardni navoj                  | acc. ISO 7-1  |
| Max. temperaturno<br>območje [°C] | 200   |