

Datum: 24.08.2024



(slika je simbolična)

Nav. priklj. 341, N.N./Z.N.Rp/R 1,č. kovanlit. ž.

Kategorija: [Union 341, taper seat, female/male](#)
Šifra: **113193RIE**

Kratek opis

Fitting 341, conical sealing, IT/ET, Rp/R 1, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust.

These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines.

Working minimal temperature = -20 °C: 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj | Rp/R 1 |
| Površina | Hot dip galvanised |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |