

Datum: 02.10.2024



(slika je simbolična)

[Nihajne varnostne spojke. I.D. 5.5ARO 210cevni priklop 6.5x10](#)

Kategorija: [Swing safety coupling DN 5.5, with hose connector](#)
Šifra: **141610RIE**

Kratek opis

Swing safety coupling I.D. 5.5, ARO 210, Steel, Hose connection 6.5x10, Operating pressure max. 25 bar, Temp. -20 °C to 100 °C

"
Swing safety coupling with free passage.
The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling.
This coupling meets ISO standard DIN EN ISO 4414, EN 983.
Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive.
"

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Delovni tlak	max. 25 bar / max. 16 bar when attaching / detaching at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	Galvanised steel
Navojni kos	Steel, QPQ treated
Ohišje	Hose connection 6.5x10
Povezava	Die-cast zinc, nickel-plated, red rubber coated
Rokav	Compressed air, gases
Srednje	NBR
Tesnilo	acc. ARO 210
Vtični profil	5.5
DN	20
a/f [mm]	63.0
Dolžina [mm]	100
Max. temperaturno območje [°C]	820 l/min (air)
Pretok	