



Okrogli cilindar, delujoč v dveh smereh, bat Ø 25, hod 160, G 1/8

Kategorija: [Metalwork](#)
Šifra: **105819RIE**

(slika je simbolična)

Kratek opis

Round cylinder, ISO 6432, double-acting, Magnet, Piston Ø 25, Stroke 160, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C

Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Bat | Synthetic (acetal) resin |
| Batnica | C45 steel, hard chrome-plated |
| Cushioning | cushioned |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Navoj na batnici | M10x1,25 |
| Oblika | Flanged joint between stainless steel barrel and heads |
| Ovoj | Stainless steel 1.4301 |
| Povezava | G 1/8 |
| Standard | acc. to ISO 6432 |
| Tesnilo | NBR |
| Min. nastavljeni tlak [bar] | 0.6 |
| Max. delovni tlak [bar] | 10 |
| Bat Ø [mm] | 25 |
| Max. temperaturno območje [°C] | 80 |
| Stroke [mm] | 160 |