

Datum: 24.08.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Okrogli cilindar, delujoč v dveh smereh, bat Ø 40, hod 160, G 1/4

Kategorija: [Metalwork](#)
Šifra: **105863RIE**

Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 40, Stroke 160, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Version with magnetic piston.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Bat | Technopolymer |
| Batnica | C45 steel, hard chrome-plated |
| Cushioning | non-cushioned |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Navoj na batnici | M12x1.25 |
| Oblika | Screwed joint between stainless steel barrel and heads |
| Ovoj | Anodised aluminium |
| Povezava | G 1/4 |
| Tesnilo | NBR |
| Min. nastavljeni tlak [bar] | 0.4 |
| Max. delovni tlak [bar] | 10 |
| Bat Ø [mm] | 40 |
| Max. temperaturno območje [°C] | 80 |
| Stroke [mm] | 160 |