

Datum: 02.10.2024



Okrogli cilinder »MI« delujoč v dveh smerehbat Ø 10hod 30M5x0.8

Kategorija: [Round cylinder, double-acting, with magnet, CA](#)
Šifra: **114788RIE**

(slika je simbolična)

Kratek opis

Round cylinder »MI« ISO 6432, double-acting, Piston Ø 10, Stroke 30, M5x0.8, Working pressure 1 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »MI« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge model
»CM« type = bottom cover with male thread, round - hinge model

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Stainless steel 1.4305
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
ET batnice	M4x0.7
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Stainless steel 1.4301
Povezava	M5x0.8
Serija	MI series
Standard	acc. to ISO 6432
Tesnilo	NBR
Vrsta	CA type
Min. delovni tlak [bar]	1
Batnica Ø [mm]	4
Bat Ø [mm]	10
Max. delovni tlak [bar]	10
Stroke [mm]	30
Max. temperaturno območje [°C]	70