

Datum: 02.10.2024



(slika je simbolična)

Okrogli cilindar TP delujoč v dveh smerehbat Ø 25hod 25G 1/8

Kategorija: [Metalwork](#)
Šifra: **105721RIE**

Kratek opis

Round cylinder TP (ISO 6432) double-acting, Piston Ø 25, Stroke 25, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 60 °C

Inexpensive standard version with aluminum pipe and magnet piston.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Batnica | C45 steel, hard chrome-plated |
| Cushioning | non-cushioned |
| Dno | Technopolymer |
| ET batnice | M10x1.25 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Glava | Technopolymer |
| Magnet | with magnet |
| Oblika | Connection: Aluminium pipe / end caps flanged |
| Ovoj | Aluminium alloy, anodised |
| Povezava | G 1/8 |
| Puša | Technopolymer |
| Serijska | TP series |
| Standard | acc. to ISO 6432 |
| Tesnilo batnice | PU |
| Min. nastavljeni tlak [bar] | 0.6 |
| Max. delovni tlak [bar] | 10 |
| Bat Ø [mm] | 25 |
| Stroke [mm] | 25 |
| Max. temperaturno območje [°C] | 60 |