

Datum: 22.07.2024



Parni lovilnik »drukodrain plus« z nivojskim nadz.230 V/50 Hz

Kategorija: [Drain for compr. air condensate »drukodrain plus«](#)
Šifra: **101626RIE**

(slika je simbolična)

Kratek opis

Condensate drain line »drukodrain plus«, Level controlled, Voltage 230 V / 50 Hz, Operating pressure 0.2 - 16 bar
Compact and exceptionally reliable, level-controlled drain for compressed air condensate.

The condensate enters the integrated collecting tank, in which the level is continuously monitored.

When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark.

Benefits of »drukodrain plus«:

- No pressure loss
- Diaphragm protected by integrated cup filter
- Test button for manual outlet
- Auto-reset function
- Suitable for all condensate types

Tehnične Specifikacije

IP zaščita	IP 65
Min. obratovalni tlak [bar]	0.2
Kapaciteta kompresorja [m ³ /min]	10
Max. obratovalni tlak [bar]	16
Zmogljivost sušenja [m ³ /min]	20
Zmogljivost filtra [m ³ /min]	100
Napetost	230 V AC / 50 Hz