

Datum: 24.08.2024

Piston rod-free cylinder ZRL1C, Ø 40, Stroke 100, Standard

Kategorija: [Rodless cylinders ZRLC](#)
Šifra: **129683RIE**

(slika je simbolična)

Kratek opis

Piston rod-free cylinder ZRL1C, Ø 40, Stroke 100, Standard, Working pressure 0,5 - 8 bar, Temp. -10 to 80 °C
ZRL1C series actuators include piston diameters of 16, 25, 32 and 40 mm with stroke lengths up to 5700 mm. Suitable for filtered (50 µm) and unlubricated or lubricated compressed air. Please ensure continuous oiling when using lubricated compressed air.
Please refer to our type code in the data-sheet for the available variants and their corresponding type designations for your individual inquiry.
Other special designs are also available on request.
After receipt of order, the cylinders will be manufactured individually for you.
Usually, shipment takes place within 5 working days, depending on the number of pieces.
Freight and packaging costs are charged individually and regardless of the value of the goods.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Cushioning	cushioned
Ffunkcija	double-acting
Magnet	with magnet
Piston caps and sliding parts	abrasion-resistant plastic
Povezava	G 1 /4
Sealing bands	Stainless steel
Tesnilo	Oil proof synthetic material (NBR)
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	8
Bat Ø [mm]	40
Max. temperaturno območje [°C]	80
Stroke [mm]	100