

Datum: 02.10.2024

Piston rod-free cylinder ZRL1F, Ø 16, Stroke 640, Standard

Kategorija: [Rodless cylinders ZRLF](#)
Šifra: **129878RIE**

(slika je simbolična)

Kratek opis

Piston rod-free cylinder ZRL1F, Ø 16, Stroke 640, Standard, Working pressure 0,5 - 8 bar, Temp. -10 to 80 °C
Piston rod-free cylinder in compact design with low carriage.
Please refer to our type code in the data-sheet for the available variants and their corresponding type designations for your individual inquiry. Other special designs are also available on request.
Suitable for filtered (50 µm) and unlubricated or lubricated compressed air. Please ensure continuous oiling when using lubricated compressed air.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Cushioning	cushioned
Ffunkcija	double-acting
Magnet	with magnet
Piston caps and sliding parts	abrasion-resistant plastic
Povezava	M5
Sealing bands	Stainless steel
Tesnilo	Oil proof synthetic material (NBR)
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	8
Bat Ø [mm]	16
Max. temperaturno območje [°C]	80
Stroke [mm]	640