

Datum: 03.11.2024

Piston rod-free cylinder ZRL1S, Ø32, stroke 1300, Standard, slow speed

Kategorija: [Rodless cylinders ZRL1S](#)
Šifra: **129848RIE**

(slika je simbolična)

Kratek opis

Piston rod-free cylinder ZRL1S, Ø 32, stroke 1300, Standard, slow speed, Working pressure 0.5 to 8 bar, Temp. -10 to 55 °C

Rodless cylinder with integrated plastic sliding. Please refer to our type code for the available variants and their corresponding type designations for your individual inquiry. Other special designs are also available on request

The integrated sliding guide allows higher loads and makes the cylinders less sensitive to moisture, dirt and shocks. Suitable for filtered (50 µm) and unlubricated or lubricated compressed air. Please ensure continuous oiling when using oiled compressed air.

Tehnične Specifikacije

| | |
|--------------------------------|------------------------------------|
| Min. temperaturno območje [°C] | -10 |
| Cushioning | cushioned |
| Ffunkcija | double-acting |
| Magnet | with magnet |
| Piston caps and sliding parts | abrasion-resistant plastic |
| Povezava | G 1 / 4 |
| Sealing bands | Stainless steel |
| Tesnilo | Oil proof synthetic material (NBR) |
| Min. delovni tlak [bar] | 0.5 |
| Max. delovni tlak [bar] | 8 |
| Bat Ø [mm] | 32 |
| Max. temperaturno območje [°C] | 55 |
| Stroke [mm] | 1300 |